

API 602 GATE VALVE with hand wheel

API 602 GLOBE VALVE with hand wheel

- outside screw and yoke, rising stem, bolted bonnet
- body/bonnet ASTM A105
- trim 13%Cr
-
- F-NPT ends as per ASME B1.20.1
- socket welded ends as per ASME B16.11
- face to face dimension as per manufacturer's standard
-
- painting: body/hand wheel – phosphorization
-
- no sign of producer on body/bonnet
- including material certificate acc. EN 10204-3.1B for body and bonnet
- including inspection certificate EN 10204-3.1B for shell test and tightness test
-

Size	Class 800			
	Note	Qty	Face to Face for gate valve	Face to Face for globe valve
1/2"	Standard port	1000	79 MM	79 MM
3/4"	Standard port	1000	92 MM	92 MM
1"	Standard port	500	111 MM	111 MM
1.1/4"	Standard port	300	120 MM	120 MM
1.1/2"	Standard port	200	120 MM	152 MM
2"	Standard port	150	140 MM	172 MM

BALL VALE as per ISO 17292

- Side entry, 3-PC type,
- full bore, solid ball
- Floating type,
- Body: ASTM A105
- Ball: A182 F304
- Stem: A182 F304
- Seat: R-PTFE
- F-NPT ends as per ASME B1.20.1
- socket welded ends as per ASME B16.11
- face to face dimension as per manufacturer's standard
-
- painting: body/hand wheel – phosphorization
- no sign of producer on body/bonnet
- including material certificate acc. EN 10204-3.1B for body and bonnet
- including inspection certificate EN 10204-3.1B for shell test and tightness test

Size	Class 800		
	Note	Qty	Face to Face
1/2"	Standard port	500	92 MM
3/4"	Standard port	500	111 MM
1"	Standard port	300	127 MM
1.1/4"	Standard port	20	140 MM
1.1/2"	Standard port	150	152 MM
2"	Standard port	150	178 MM