

400V|50Hz|3Phase|Pf.:0.8
POWERED BY CHONGQING CUMMINS

| Model | ESP | | PRP | | Engine Model | Cyl | Gov | Dis (L) | Dimension L*W*H (MM) | |
|--------------|------|-----|------|-----|--------------|-----|-----|---------|----------------------|----------------|
| | kVA | kW | kVA | kW | | | | | Open | Silent |
| WD275C/S-II | 275 | 220 | 250 | 200 | NT855-GA | 6L | E | 14 | 3000*1100*1850 | 4300*1400*2150 |
| WD275C/S-III | 275 | 220 | 250 | 200 | NT855-G1 | 6L | E | 14 | 3000*1100*1850 | 4300*1400*2150 |
| WD303C/S-I | 303 | 242 | 275 | 220 | NTA855-G1A | 6L | E | 14 | 3100*1100*1850 | 4300*1400*2150 |
| WD344C/S | 344 | 275 | 313 | 250 | NTA855-G1B | 6L | E | 14 | 3100*1100*1850 | 4300*1400*2150 |
| WD344C/S-I | 344 | 275 | 313 | 250 | NTA855-G2 | 6L | E | 14 | 3100*1100*1850 | 4300*1400*2150 |
| WD378C/S | 378 | 303 | 344 | 275 | NTA855-G2A | 6L | E | 14 | 3100*1100*1850 | 4300*1400*2150 |
| WD385C/S | 385 | 308 | 350 | 280 | NTA855-G4 | 6L | E | 14 | 3100*1100*1850 | 4300*1400*2150 |
| WD413C/S-I | 413 | 330 | 375 | 300 | NTAA855-G7 | 6L | E | 14 | 3300*1250*1850 | 4500*1600*2150 |
| WD454C/S | 454 | 363 | 413 | 330 | NTAA855- | 6L | E | 14 | 3300*1250*1850 | 4500*1600*2150 |
| WD413C/S-II | 413 | 330 | 375 | 300 | KTA19-G2 | 6L | E | 18.9 | 3400*1258*2050 | 4700*1900*2150 |
| WD495C/S-II | 495 | 396 | 450 | 360 | KTA19-G3 | 6L | E | 18.9 | 3400*1258*2050 | 4700*1900*2150 |
| WD550C/S-2 | 550 | 440 | 500 | 400 | KTA19-G3A | 6L | E | 18.9 | 3400*1258*2050 | 4700*1900*2150 |
| WD550C/S-3 | 550 | 440 | 500 | 400 | KTA19-G4 | 6L | E | 18.9 | 3400*1258*2050 | 4700*1900*2150 |
| WD578C/S | 578 | 462 | 525 | 420 | KTA19-G5 | 6L | E | 18.9 | 3700*1570*2080 | 5000*1900*2150 |
| WD633C/S | 633 | 506 | 575 | 460 | KTAA19-G6 | 6L | E | 18.9 | 3700*1570*2050 | 5000*1900*2150 |
| WD688C/S | 688 | 550 | 625 | 500 | KTAA19-G6A | 6L | E | 18.9 | 3700*1570*2080 | 5000*1900*2150 |
| WD660C/S-I | 660 | 528 | 600 | 480 | KTA19-G8 | 6L | E | 18.9 | 3700*1570*2080 | 5000*1900*2150 |
| WD688C/S-I | 688 | 550 | 625 | 500 | KTA38-G | 12 | E | 37.8 | 4550*1700*2320 | 6200*2200*2550 |
| WD798C/S | 798 | 638 | 725 | 580 | KTA38-GA | 12 | E | 37.8 | 4550*2100*2320 | 6200*2200*2550 |
| WD784C/S | 784 | 627 | 713 | 570 | KTA38-G1 | 12 | E | 37.8 | 4550*2100*2320 | 6200*2200*2550 |
| WD825C/S | 825 | 660 | 750 | 600 | KTA38-G2 | 12 | E | 37.8 | 4550*2100*2320 | 6200*2200*2550 |
| WD880C/S | 880 | 704 | 800 | 640 | KTA38-G2B | 12 | E | 37.8 | 4550*2100*2320 | 6200*2200*2550 |
| WD1001C/S | 1001 | 801 | 910 | 728 | KTA38-G2A | 12 | E | 37.8 | 4550*2100*2320 | Containerised |
| WD1100C/S | 1100 | 880 | 1000 | 800 | KTA38-G5 | 12 | E | 37.8 | 4650*2100*2320 | Containerised |

Remarks:

- (1) also available in the following voltages:440/245V,416/240V,380/220V and 220/127V;
 (2) ESP:Standby power standby duty,operation under variable load without over load;
 (3) PRP:Prime power-Continuous duty operation,under variable load 24/24h-10% over load permissible 1hour/12hours;
 (4)M:Mechanical speed governor,E/Ecu: Electronic speed governor;
 The data is only for your reference but not for use of sales.