

GENERATOR SET|TECHNICAL SHEET

	ROLLER SELECTION 7	TABLE						
CONTR	OLLER SPECIFICATION							
		$\mathbf{W}\mathbf{D}^{^{+}}\mathbf{I}$	WD ⁺ PLC1.0		WD⁺ PLC2.0		WD⁺ PLC3.0	
Model Function			HGM		DSE7320		DSE	
		6110N	6120N	MKII	MKII	MKII	8620	
		Standard	Option	Standard	Option	Standard	Option	
Manufacturer		SMAR	SMARTGEN		DEE		PSEA	
AMF		×	•	×	•	Auto Start	•	
ECU		0	0	•	•	•	•	
Cummunication Port		U	USB		RS232/485/USB		RS232/485/USB/ Ethernet	
Monitor Function	Generator Set Voltage	•	•	•	•	•	•	
	Generator Set Current	•	•	•	•	•	•	
	Generator Set Frequency	•	•	•	•	•	•	
	Generator Set Speed	•	•	•	•	•	•	
	Generator Set Output Powe	er •	•	•	•	•	•	
	Generator Set Power Factor	r •	•	•	•	•	•	
	Generator Set Run Hours	•	•	•	•	•	•	
	Oil Pressure	•	•	•	•	•	•	
	Water Temperature	•	•	•	•	•	•	
	Battery Voltage	•	•	•	•	•	•	
	Fuel Level	•	•	•	•	•	•	
	Mains Voltage	×	•	×	•	•	•	
	Mains Frequency	×	•	×	•	•	•	
	Mains Current	×	•	×	•	•	•	
	Synchronising	×	×	×	×	•	•	
	Mains Parallel Operation	×	×	×	×	•	•	
Protection	Low Oil Pressure	•	•	•	•	•	•	
	Water Temperature High	•	•	•	•	•	•	
	Over Speed	•	•	•	•	•	•	
	Battery Charge Failure	•	•	•	•	•	•	
	Reverse Power	×	×	×	×	•	•	
Application		×	AMF+ATS	×	AMF+ATS	Multiple Island or Single Parallel to Mains	Single Parallel t Mains	

 $[\]bullet \ Standard \ \circ Optional \ \times Impossible$

