

POWERED BY FAWDE

Model	ESP		PRP		Engine Model	Cyl	Gov	Dis (L)	Dimension L*W*H (MM)	
	kVA	kW	kVA	kW					Open	Silent
WD21F/S	21	17	19	15	4DW81-28D	4L	M	2.27	1350*750*1050	2000*860*1050
WD30F/S	30	24	28	22	4DW91-38D	4L	M	2.54	1450*750*1050	2100*940*1090
WD34F/S	34	28	31	25	4DW92-42D	4L	M	2.54	1700*750*1100	2100*940*1090
WD34F/S-I	34	28	31	25	4DW92-45D	4L	M	2.54	1700*750*1100	2100*940*1090
WD41F/S	41	33	38	30	4DW93-50D	4L	E	2.54	1700*750*1100	2200*990*1290
WD41F/S-I	41	33	38	30	4DX21-53D	4L	M	3.86	1700*750*1100	2200*990*1290
WD50F/S	50	40	45	36	4DX21-61D	4L	E	3.86	1800*750*1150	2200*990*1290
WD48F/S	48	39	44	35	4DX22-60D	4L	M	3.86	1800*750*1150	2200*990*1290
WD62F/S	62	50	56	45	4DX22-75D	4L	E	3.86	2000*750*1200	2380*990*1300
WD69F/S	69	55	63	50	4DX23-82D	4L	M	3.86	2000*750*1200	2380*990*1300
WD76F/S	76	61	69	55	4DX23-90D	4L	E	3.86	2150*750*1200	3000*1130*1670
WD89F/S	89	72	81	65	4110/125Z-11D	4L	E	4.75	2300*1000*1500	3200*1130*1670
WD117F/S	117	94	106	85	CA4F2-14D	4L	E	6.55	2350*1000*1500	3200*1130*1670
WD131F/S	131	105	119	95	6CDF2D-16D	6L	M	6.55	2550*1000*1600	3400*1100*1800
WD151F/S	151	121	138	110	CA6DF2-18D	6L	M	7.13	2700*1000*1800	3700*1100*2000
WD179F/S	179	143	163	130	CA6DF2-21D	6L	E	8.57	2750*1000*1800	3700*1100*2000
WD227F/S	227	182	206	165	CA6DL1-27D	6L	E	8.57	3000*1120*1900	3700*1100*2000
WD275F/S	275	220	250	200	CA6DL2-32D	6L	E	11.4	3000*1120*1900	4200*1400*2000
WD371F/S	371	297	338	270	CA6DM2J-42D	6L	E	12.53	3000*1120*1900	4200*1400*2000
WD413F/S	413	330	375	300	CA6DN1J-45D	6L	E	12.53	3000*1120*1900	4200*1400*2000

Remarks:

- (1) also available in the following voltages:480/277V,440/254V,380/220V and 240/139V;
 - (2) ESP:Standby power standby duty,operation under variable load without over load;
 - (3) PRP:Prime power-Continuous duty operation,under variable load 24/24h-10% over load permissible 1hour/12hours;
 - (4)M:Mechanical speed governor,E/Ecu: Electronic speed governor;
- The data is only for your reference but not for use of sales.