

POWERED BY UK/USA PERKINS

Model	ESP		PRP		Engine Model	Cyl	Gov	Dis (L)	Dimension L*W*H (MM)	
	kVA	kW	kVA	kW					Open	Silent
WD40P/S	40	32	37	29	404D-22TAG	4L	E	2.2	1200*750*950	1900*860*1020
WD110P/S	110	88	100	80	1104C-44TAG2	4L	E	4.4	1200*750*950	1900*860*1020
WD248P/S	248	198	225	180	1206A-E70TTAG1	6L	E	6.6	1300*750*1100	2100*860*1020
WD388P/S	388	310	353	282	1506A-E88TAG5	6L	E	8.8	1400*750*950	2100*860*1020
WD440P/S	440	352	400	320	2206C-E13TAG2	6L	E	12.5	2000*850*1200	2600*1000*1450
WD550P/S	550	440	500	400	2506C-E15TAG1	6L	E	15	2000*850*1200	2600*1000*1450
WD688P/S	688	550	625	500	2806C-E18TAG1A	6L	E	18.1	2000*850*1200	2600*1000*1450

POWERED BY INDIA PERKINS

WD825P/S	825	660	750	600	4006-23TAG2A	6L	E	22.92	4300*1700*250	5800*2200*2550
WD935P/S	935	748	850	680	4006-23TAG3A	6L	E	22.92	4300*1700*250	5800*2200*2550
WD1100P/S	1100	880	1000	800	4008TAG2	8L	E	30.6	4700*2000*250	Containerised
WD1378P/S	1378	1102	1253	1002	4012-46TWG2A	12V	E	45.8	4800*1800*250	Containerised
WD1650P/S	1650	1320	1500	1200	4012-46TAG2A	12V	E	45.8	5000*2200*253	Containerised
WD1856P/S	1856	1485	1688	1350	4012-46TAG3A	12V	E	45.8	5100*2200*253	Containerised

Remarks:

- (1) also available in the following voltages:480/277V,440/254V,380/220V and 240/139V;
- (2) ESP:Standby power standby duty,operation under variable load without over load;
- (3) PRP:Prime power-Continuous duty operation,under variable load 24/24h-10% over load permissible 1hour/12hours;
- (4)M:Mechanical speed governor,E/Ecu: Electronic speed governor;

The data is only for your reference but not for use of sales.