

POWERED BY PORTABLE PETROL ENGINE

Features:

- Powerful commercial level WD+ 4-stroke gasoline engine with low vibration, low CO & NO emission
- Suit for 50% hardenite dirty water,mud slurry; such as building operation, emergency road repair exhaust and so on; also could use as clean water pump.



SPECIFICATION&SELECTION SHEET

Model	WD50P	WD80P	WD100P
Type	Self-priming,Centrifugal Pump		
Inlet (mm)	50(2inch)	80(3inch)	100(4inch)
Outlet (mm)	50(2inch)	80(3inch)	100(4inch)
Potate Speed (rpm)	3600		
Max. Lift Head (m)	30	30	25
Max. Flow (l/h)	27000(27M ³ /H)	60000(60M ³ /H)	80000(80M ³ /H)
Suction (m)	7		
Engine Model	P168F	P168F-II	P188F
Engine Type	Single-cylinder,Air-cooled,4-stroke,OHV Petrol Engine		
Displacement Capacity	163	208	389
Max.Output (hp)	5.5	6.5	13
Fuel tank Capacity (L)	3.6	3.6	6.5
Lubrication Oil	SAE10W/30	SAE10W/30	SAE10W/30
Lubrication Oil Volume(L)	0.6	0.6	1.1
Starting System	Standard:Recoil Start / Option:Electric Start		
Dim (LXWXH) (mm)	485X390X420	515X390X445	630X455X500
Net Weight / Gross Weight (kg)	25/27	27/29	44/46