

400V|50Hz|3Phase|Pf.:0.8
POWERED BY YANGDONG

Model	ESP		PRP		Engine Model	Cyl	Gov	Dis (L)	Dimension L*W*H (MM)	
	kVA	kW	kVA	kW					Open	Silent
WD11YD/S	11	9	10	8	YD380D	3L	M	1.352	1300*700*1000	1900*860*1020
WD11YD/S-I	11	9	10	8	YD385D	3L	M	1.532	1300*700*1000	1900*860*1020
WD14YD/S	14	11	13	10	YD480D	4L	M	1.809	1300*700*1000	1900*860*1020
WD17YD/S	17	13	15	12	YD4KD	4L	M	2.043	1400*700*1000	2000*860*1020
WD18YD/S	18	14	16	13	YND485D	4L	M	2.156	1400*700*1000	2000*860*1020
WD22YD/S	22	18	20	16	YND490D	4L	M	2.417	1400*700*1000	2000*860*1020
WD22YD/S-I	22	18	20	16	YSD490D	4L	M	2.543	1400*700*1000	2000*860*1020
WD28YD/S	28	22	25	20	Y490D	4L	M	2.672	1500*700*1000	2100*860*1120
WD28YD/S-I	28	22	25	20	Y495D	4L	M	2.977	1500*700*1000	2100*860*1120
WD33YD/S	33	26	30	24	Y4100D	4L	M	3.707	1600*800*1050	2200*910*1120
WD36YD/S	36	29	33	26	Y4102D	4L	M	3.857	1700*800*1050	2200*910*1120
WD41YD/S	41	33	38	30	Y4105D	4L	M	4.1	1750*800*1100	2200*910*1120
WD44YD/S	44	35	40	32	Y4102ZD	4L	M	3.857	1800*800*1100	2300*960*1300
WD55YD/S	55	44	50	40	Y4102ZLD	4L	M	3.857	1800*800*1100	2300*960*1300
WD66YD/S	66	53	60	48	Y4105ZLD	4L	E	4.1	1850*800*1100	2400*960*1300
WD69YD/S	69	55	63	50	YD4EZLD	4L	E	4.1	1850*800*1100	2400*960*1300
WD88YD/S	88	70	80	64	Y4110ZLD	4L	E	4.484	1900*800*1100	2600*960*1300

Remarks:

(1) also available in the following voltages:440/245V,416/240V,380/220V and 220/127V;

(2) ESP:Standby power standby duty,operation under variable load without over load;

(3) PRP:Prime power-Continuous duty operation,under variable load 24/24h-10% over load permissible 1hour/12hours;

(4)M:Mechanical speed governor,E/Ecu: Electronic speed governor;

The data is only for your reference but not for use of sales.