

440V|60Hz|3Phase|Pf.:0.8
POWERED BY YANGDONG

Model	ESP		PRP		Engine Model	Cyl	Gov	Dis (L)	Dimension L*W*H (MM)	
	kVA	kW	kVA	kW					Open	Silent
WD13YD/S	13	10	12	9.5	YD380D	3L	M	1.352	1300*700*1000	1900*860*1020
WD14YD/S	14	11	13	10	YD385D	3L	M	1.532	1300*700*1000	1900*860*1020
WD18YD/S	18	14	16	13	YD480D	4L	M	1.809	1300*700*1000	1900*860*1020
WD21YD/S	21	17	19	15	YD4KD	4L	M	2.043	1400*700*1000	2000*860*1020
WD22YD/S	22	18	20	16	YND485D	4L	M	2.156	1400*700*1000	2000*860*1020
WD28YD/S	28	22	25	20	YND490D	4L	M	2.417	1400*700*1000	2000*860*1020
WD28YD/S-I	28	22	25	20	YSD490D	4L	M	2.543	1400*700*1000	2000*860*1020
WD32YD/S	32	25	29	23	Y490D	4L	M	2.672	1500*700*1000	2100*860*1020
WD33YD/S	33	26	30	24	Y495D	4L	M	2.977	1500*700*1000	2100*860*1020
WD37YD/S	37	30	34	27	Y4100D	4L	M	3.707	1600*800*1050	2200*910*1120
WD41YD/S	41	33	38	30	Y4102D	4L	M	3.857	1650*800*1050	2200*910*1120
WD50YD/S	50	40	45	36	Y4105D	4L	M	4.1	1700*800*1050	2200*910*1120
WD55YD/S	55	44	50	40	Y4102ZD	4L	M	3.857	1750*800*1100	2300*960*1120
WD58YD/S	58	46	53	42	Y4102ZLD	4L	M	3.857	1800*800*1100	2300*960*1300
WD69YD/S	69	55	63	50	Y4105ZLD	4L	E	4.1	1800*800*1050	2400*960*1300
WD77YD/S	77	62	70	56	YD4EZLD	4L	E	4.1	1850*800*1050	2400*960*1300
WD96YD/S	96	77	88	70	Y4110ZLD	4L	E	4.484	1900*800*1050	2600*960*1300

Remarks:

- (1) also available in the following voltages:480/277V,440/254V,380/220V and 240/139V;
 - (2) ESP:Standby power standby duty,operation under variable load without over load;
 - (3) PRP:Prime power-Continuous duty operation,under variable load 24/24h-10% over load permissible 1hour/12hours;
 - (4)M:Mechanical speed governor,E/Ecu: Electronic speed governor;
- The data is only for your reference but not for use of sales.